Canon

Canon imageRUNNER ADVANCE C255i Laser A4 1200 x 1200 DPI 25 ppm Wifi

Famille de produit: imageRUNNER Marque: Canon Code produit: 1406C001

Nom du produit : C255i

Canon imageRUNNER ADVANCE C255i. Technologie d'impression: Laser, Impression: Impression mono, Résolution maximale: 1200 x 1200 DPI. Copier: Copie simple, Résolution max. des copies: 600 x 600 DPI. Numérisation: Numérisation couleur, Résolution de numérisation optique: 600 x 600 DPI. Télécopier: Télécopie simple. Taille de papier de série A ISO maximum: A4. Wifi. Impression directe. Couleur du produit: Blanc



Printing		Paper handling	
Duplex printing mode	Auto	Multi-Purpose Tray media weight	60 - 220 g/m²
Print technology *	Laser	Duplex media weight	60 - 163 g/m²
Printing *	Mono printing	Ports & interfaces	
Duplex printing * Maximum resolution *	✓ 1200 x 1200 DPI	Standard interfaces	Ethernet, USB 2.0, USB 3.2 Gen 1 (3.1 Gen 1), Wireless LAN
Print speed (black, normal quality, A4/US Letter) *	25 ppm	Direct printing *	✓
Warm-up time	30 s	USB port	✓
Warm-up time (from sleep mode)	10 s	USB 3.2 Gen 1 (3.1 Gen 1) ports quantity	1
Copying		Optional connectivity	Bluetooth, Near Field Communication (NFC)
Duplex copying *	Mana anning	Network	
Copying * Maximum copy resolution *	Mono copying 600 x 600 DPI	Wi-Fi *	✓
Copy speed (black, normal quality,		Ethernet LAN *	v
A4)	25 cpm	Cabling technology	10/100Base-T(X)
Time to first copy (black, normal)	6.9 s	Ethernet LAN data rates	10,100 Mbit/s
Maximum number of copies	999 copies	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Copier resize	25 - 400%	Email protocols	POP3, SMTP
Scanning		Performance	
Duplex scanning *	✓	Internal storage capacity	250 GB
Scanning *	Colour scanning	Internal memory *	3000 MB
Optical scanning resolution * Scanner type *	600 x 600 DPI Flatbed & ADF scanner	Built-in processor	✓
Scan to	E-mail, FTP, File, SMB	Processor frequency	1750 MHz
Scan speed (black)	50 inch/min	Processor cores	2
Image formats supported	EPS, JPG, TIF	Sound pressure level (printing)	63.2 dB
Document formats supported	PDF, XPS	Sound power level (standby)	48.7 dB
Scan drivers	TWAIN, WIA	Design	
Fax		Product colour *	White
Faxing *	Mono faxing	Market positioning *	Business
Fax resolution (black)	400 x 400 DPI	Built-in display *	✓
Modem speed	33.6 Kbit/s	Display	TFT 25.6 x x (10.11)
Fax memory	30000 pages	Display diagonal	25.6 cm (10.1")
Speed dialling	✓	Touchscreen	✓ Touch
Fax speed dialing (max numbers)	200	Control type	Touch ✓
Fax broadcasting	256 locations	Colour display	•
Features			
Page description languages	PCL 6, PostScript 3, UFRII		

Fontures		Dower	
Features		Power	
Printer fonts Bitmap fonts	Barcode, Bitmap, PCL, PostScript OCR-A, OCR-B, Roman	Power consumption (average operating)	1500 W
Number of PCL fonts	93	Power consumption (printing)	488 W
Number of PostScript fonts	136	Power consumption (standby)	40.3 W
Number of bitmap fonts	10	Power consumption (sleep)	0.8 W
·		Power consumption (off)	0.1 W
Input & output capacity		Energy Star Typical Electricity	0.7 kWh/week
Total input capacity *	550 sheets	Consumption (TEC)	220 240 1/
Total output capacity *	250 sheets	AC input voltage	220 - 240 V
Multi-Purpose tray	•	AC input frequency	50 - 60 Hz
Multi-Purpose tray input capacity	100 sheets	System requirements	
Paper input type	Cassette	Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Vista, Windows Vista Business
Maximum input capacity Maximum output capacity	2300 sheets 500 sheets		
Paper handling	500 Sinecis		Mac OS X 10.6 Snow Leopard, Mac
		Mac operating systems supported	OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Maximum ISO A-series paper size *	A4 Rand namer Envelopes Plain namer		
Paper tray media types *	Bond paper, Envelopes, Plain paper, Pre-printed, Recycled paper, Thick paper, Thin paper	Server operating systems supported	Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2,
Multi numaca trav madia tunas	Bond paper, Envelopes, Labels, Plain paper, Recycled paper, Thick paper, Thin paper, Transparencies A4, A5 B5 98 - 148 mm	Windows Server 2012 R2,	
Multi-purpose tray media types		Operational conditions	
ISO A-series sizes (A0A9) *		Operating relative humidity (H-H)	20 - 80%
ISO B-series sizes (B0B9)		Operating temperature (T-T)	10 - 30 °C
Custom media width		Sustainability	
Custom media length	216 - 355.6 mm	•	DI A A A A LA ENERGY STAR
Paper tray media weight	60 - 163 g/m²	Sustainability certificates	Blue Angel, ENERGY STAR
		Weight & dimensions	
		Width	511 mm
		Depth	651 mm
		Height	639 mm
		Weight	49 kg
		Technical details	
		Compliance certificates	RoHS
		Other features	
		Fonts included	✓

